

PAT300 series

Portable Appliance Testers



- **Simple manual or automatic testing**
- **Bond testing at 25 A, 10 A and 200 mA**
- **Differential, touch and substitute leakage testing**
- **Full colour display**
- **Tests portable RCDs and extension leads**
- **Pre-set test sequences for Class I, Class II and extension leads**
- **Flash Testing at 1.5 kV and 3 kV**
- **Tests to DIN VDE 0701-0702**

DESCRIPTION

An easily portable desktop appliance tester for testing the safety of portable electrical equipment to meet health and safety regulations. The PAT300 series are fully featured testers with dedicated test buttons for direct access to tests. They are designed for customers who do not require the complexity of a fully configurable database of clients and results within the tester but do need a complete range of functions to allow automatic or manual testing of the widest range of electrical assets. There are two products in the range - the PAT320 and the PAT350. The PAT350 is identical to the PAT320, with the addition of flash-test capability for use in environments such as manufacturing, production or tool-hire shops.

Simple push-button operation make the PAT300s fast and intuitive in use. All regulatory test requirements are supported, including Class I and Class II, IEC power leads, extension leads and full tests for portable RCDs. An automatic mode is available for Class I and Class II testing. In automatic mode, the tests proceed sequentially through bond, insulation and operation, indicating a pass or fail at each test. If a fail occurs, testing is stopped. When manual testing, each test is preceded by a selection screen where the test parameters are selected, such as bond test current, insulation test voltage or leakage test type. These diagnostic buttons provide direct access to any test individually, allowing single tests to be performed following repair or a suspect result.

Accessories supplied with all models include a combined earth-bond and insulation test lead, an adaptor for testing extension leads, and a carry-case convenient product and lead storage.

APPLICATION

There is a legal requirement for any landlord, employer or owner of a place of work or public place, to ensure that all electrical equipment accessible by tenants, employees or the public is maintained in a safe condition, and an acceptable method of ensuring this is by routine electrical testing. This can be performed by electrical contractors, specialist PAT testing organisations, maintenance departments, or facilities management companies.

The PAT300 range is suitable for performing portable appliance testing in locations such as hotels, public houses, schools, colleges, nurseries, shops, offices, theatres, banks, restaurants, cafés, sports and leisure facilities, cinemas, factories and hair salons etc. The PAT350 is suitable for use in tool-hire shops where equipment is routinely tested prior to hire, and will perform a flash test in addition to standard PAT tests.

SPECIFICATIONS

Electrical supply range

230 V $\pm 10\%$ ± 1 V @ 50 Hz $\pm 10\%$ ± 0.1 Hz
Instrument accuracy cannot be guaranteed when operated on supply frequencies other than those specified above

Bond test

(10 A and 25 A)

Open circuit voltage:

9 V a.c. $\pm 10\%$ ± 0.1 V (Supply: 230 V 50 Hz)

Earth bond resistance accuracy:

$\pm 5\%$ ± 3 digits (0 to 0.49 Ω)

$\pm 5\%$ ± 5 digits (0.5 to 1.99 Ω)

Earth bond resistance resolution:

10 m Ω (0 to 1.99 Ω)

Display range: 10 to 1.99 Ω

Continuity

Continuity test voltage:

4.0 V d.c. -0% +10

Continuity resistance accuracy:

$\pm 5\%$ ± 3 digits (0 to 0.49 Ω)

$\pm 5\%$ ± 5 digits (0.5 to 19.99 Ω)

Continuity resistance resolution:

10 m Ω (1 to 19.99 Ω)

Display range: 0 to 19.99 Ω

Insulation test

(250 V and 500 V)

Insulation resistance accuracy (230 V):

$\pm 2\%$ ± 5 digits (0 to 19.99 M Ω)

$\pm 5\%$ ± 10 digits (20 to 99.99 M Ω)

Insulation resistance resolution:

0.01 M Ω

Display range: 0 to 99.99 M Ω

Substitute leakage current

Test voltage and frequency: 40 V a.c. $\pm 10\%$ @ nominal mains frequency

Leakage current accuracy: $\pm 5\%$ ± 5 digits

Leakage current resolution: 0.01 mA

Display range: 0 to 19.99 mA

Leakage current

Test voltage: Nominal mains supply

Differential leakage current accuracy: $\pm 5\%$ ± 5 digits

Differential leakage current resolution: 0.01 mA

Display range: 0 to 19.99 mA

Touch current test

Test voltage: Nominal main supply

Touch current accuracy: $\pm 5\%$ ± 5 digits

Touch current resolution: 0.01 mA

Display range: 0.00 to 10 mA

Operational test

Test voltage: Nominal mains supply.

VA Accuracy:

$\pm 5\%$ ± 10 digits (0 to 99 VA)

$\pm 5\%$ ± 50 digits (100 VA - 999 VA)

$\pm 5\%$ ± 100 digits (1000 VA - 3700 VA)

Resolution: 1 VA (0 to 3700 VA)

Display range: 0 to 3.99 KVA

Ext Lead Test

Test performed: Bond insulation and polarity.

Polarity test voltage: 12 V dc

Polarity:

Lead OK

Live neutral S/C

Live neutral reversed

Live/neutral O/C

Flash test

(PAT350)

Flash test voltage:

1500 V a.c nominal for Class I

3000 V a.c nominal for Class II

Flash test current:

< 3.5 mA short circuit @ 253 V primary supply voltage

Flash test breakdown current accuracy:

$\pm 5\%$ ± 5 digits

Flash test breakdown current resolution:

0.01 mA

Display range: 0 to 3.0 mA

RCD tests

RCD test voltage and frequency: Nominal mains supply

Test current accuracy:

-8% to -2% ($i_r \times I$)

+2% to +8% ($1 \times I, 5 \times I$)

Trip time accuracy: $\pm 1\%$ ± 5 digits

Trip time resolution: 0.1 ms

Display range:

0 to 1999 ms ($i_r \times I$)

0 to 300 ms ($1 \times I$)

0 to 40 ms ($5 \times I$)

Fuse Test

Test voltage: 3.3 V

Warning: Audible beep if fuse is OK

Operating temperature range and humidity -10 to +50 °C

90% RH @ -10 to +30 °C

75% RH @ +30 to +50 °C

Storage temperature range and humidity -20 to +60° C

90% RH @ -10 to +30 °C

75% RH @ +30 to +50 °C

Weight

PAT310 (with packaging) 3.2 kg

PAT320 (with packaging) 4.9 kg

PAT350 (with packaging) 5.5 kg

Dimensions

210 mm (H) x 280 mm (W) x 390 mm (L)

Dimensions (instrument and case)

PAT310 120 mm (H) x 255 mm (W) x 320 mm (L)

PAT320

155mm (H) x 255 mm (W) x 320 mm (L)

PAT350

155mm (H) x 255 mm (W) x 320 mm (L)

Maximum altitude

2,000 m

IP rating

IP40

Safety	IEC 61010-1: CAT II 300V
EMC	IEC 61326-1: 2006
	IEC 61326-2-2: 2005.

ORDERING INFORMATION

Description	Order Code	Description	Order Code
PAT310-EU	1000-742		
PAT350-EU	1000-953		
Included accessories		Optional accessories	
Printed quick start guide		415 V adaptor lead (4-pin) to SC (CEE7/7) (16 A)	1001-232
Full user guide on CD		415 V adaptor lead (5 pin) to SC (CEE7/7) (16 A)	1000-768
Calibration certificate		Roll of 1000 FAIL test labels	1000-771
Continuity/earth bond lead	1001-233	Roll of 1000 PASS test labels	1001-227
Extension lead adaptor Schuko	1001-235	PAT accessory pouch	1000-971
Flash test lead	5310-401	PAT test certificate book	2001-044
Carry case with lead/document pouch	2000-962	Screen protector (2)	1001-299
			1002-572

UK
Archcliffe Road Dover
CT17 9EN England
T +44 (0) 1304 502101
F +44 (0) 1304 207342
UKsales@megger.com

UNITED STATES
4271 Bronze Way
Dallas TX 75237-1019 USA
T 800 723 2861 (USA only)
T +1 214 333 3201
F +1 214 331 7399
USsales@megger.com

OTHER TECHNICAL SALES OFFICES
Valley Forge USA, College Station USA,
Sydney AUSTRALIA, Danderyd SWEDEN,
Ontario CANADA, Trappes FRANCE,
Oberursel GERMANY, Aargau SWITZERLAND,
Kingdom of BAHRAIN, Mumbai INDIA,
Johannesburg SOUTH AFRICA, Chonburi THAILAND

CERTIFICATION ISO
Registered to ISO 9001:2000 Cert. no. Q 09290

PAT300EU_DS_en_V05
www.megger.com
Megger is a registered trademark